# Product Name: Insitu® Gray Waterborne Primer

**Product Code: WRA-AC-075**  Date issued: 8/24/2023

CONFIDENTIAL

### **SECTION 1: IDENTIFICATION**

Product Name Insitu Gray Waterborne Primer

WRA-AC-075 Product Code #

Identified Uses Protective Coating

Manufacturer: Modine Mfg Company 1423 West Ormsby Ave. Louisville, KY 40210

Emergency Contact Number: Day: 703-527-3887 CHEMTREC Night: : 703-527-3887 CHEMTREC

### SECTION 2 : HAZARDS IDENTIFICATION

**GHS** Classification

Acute Toxicity - Oral 4 & 5 Acute Toxicity-Dermal 4 Eye Damage/Irritation 2A Acute Toxicity - Inhalation 4

### **GHS Label Elements**

#### Hazard Symbols



Signal Word Warning

### **Hazard Statements**

H302 Harmful if swallowed H312 Harmful in contact with skin H319 Causes serious eye irritation H332 Harmful if inhaled

#### **Precautionary Statements**

### Prevention

P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust/fume/gas/mist/vapor/spray. P264 Wash hands and/or face thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in well-ventilated area.

#### Response

P312 Call a poison center or doctor if you feel unwell.

P330 If swallowed, rinse mouth.

P301 + P310 If swallowed: Immediately call a poison center or doctor.

P302 + P350 IF ON SKIN: Gently wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Storage/ Disposal

P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.

**Other Hazards** OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

# SECTION 3: COMPOSITION INFORMATION

# SAFETY DATA SHEET

# Product Name: Insitu® Gray Waterborne Primer Product Code: WRA-AC-075

Chemical Designation	CAS No.	% by Weight
itanium dioxide	13463-67-7	12.60
magnesium silicate	14807-96-6	5.52
2-butoxyethanol	111-76-2	3.42
propylene glycol	57-55-6	1.01
attapulgite clay	12174-11-7	0.96
sodium nitrite	7632-00-0	0.10
carbon black	1333-86-4	0.10

### SECTION 4: FIRST AID MEASURES

General Advice	Show this safety data sheet to the doctor in attendance
Eyes:	Flush with plenty of cool water for at least15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate
	medical attention.
Skin:	Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.
Inhalation:	Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.
Ingestion:	Do not induce vomiting – seek immediate medical attention.
Notes to Physician	Treat symptomatically

# SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific Hazards arising	Closed containers may rupture if exposed to fire or extreme heat.
from the Chemical	
Special protective	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective
Equipment:	gear.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental	Use personal protective equipment. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from
Precautions	entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages
Methods for Clean-up	cannot be contained. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface
Other Information	thoroughly. None known

# SECTION 7 : HANDLING & STORAGE

 Handling:
 Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

 Storage:
 Keep container tightly closed. Keep out of the reach of children.

# SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 110

HMIS CODE: 4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD,

\* - Chronic Hazard Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

Exposure Limits Hazardous Components

OSHA PEL ACGIH TLV

2

Date issued: 8/24/2023

# Product Name: Insitu® Gray Waterborne Primer Product Code: WRA-AC-075

# Date issued: 8/24/2023

- - - -

titanium dioxide	15 mg/m3	10 mg/m3
magnesium silicate	20 mppcf	2 mg/m3 (R)
2-butoxyethanol	50 ppm	20 ppm
propylene glycol	NE	NE
carbon black	3.5 mg/m3	3 mg/m3 (I)

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit (R) = Respirable fraction

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipmen	.t
Eyes/Face:	Safety goggles or full face shield
Skin:	Protective gloves and impervious clothing.
<b>Respiratory Protection:</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
Hygiene Practices:	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

handling.

Appearance:	liquid		
Odor:	Little or no odor	Odor threshold:	Not determined
VOC lb/gal	0.45	VOC (g/L)	53.59
VOC (lb/gal) less exempt	1.10	VOC (g/L) less exempt	132.04
Relative Density (LB/GAL):	9.92	Specific Gravity (g/L):	1.19
Flash Point (F):	Greater than 201		
Flammability:	Not applicable	Upper/lower flammability limits:	Not applicable
Auto-ignition temperature:	Not applicable	Decomposition temperature:	Not determined
Evaporation rate :	Not available		
Vapor Pressure (mmHg) :	Not available	Vapor Density :	Not available
Initial Boiling Point (F):	212	Boiling Point Range (F):	Not available
Freezing Point (F):	32	Melting Point (F):	Not determined
pH	Not available	Viscosity	Not available
Solubility (ies):	Not determined		
Partition coefficient: n-	Not determined		
octanol/water			

### SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:	Stable under normal conditions.
Conditions to Avoid:	Prevent from freezing
Materials to Avoid:	No materials to be especially mentioned.
Hazardous Decomposition Products:	None under normal use.
Possibility of Hazardous Reactions:	None under normal conditions of use.

# SECTION 11: TOXICOLOGICAL INFORMATION

<u>Acute Toxicity</u> Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
titanium dioxide	10,000	10,000	6.82
magnesium silicate	NA	NA	NA
2-butoxyethanol	470	220	2.2
propylene glycol	NA	NA	NA
carbon black	15,400	3,000	NA

# Chronic Toxicity

The information below indicates whether each agency has listed any ingredient as a carcinogen: Component IARC NTP

OSHA

# SAFETY DATA SHEET

# Product Name: Insitu® Gray Waterborne Primer Product Code: WRA-AC-075

carbon black 2B – Possible Human Carcinogen Not listed Listed	Listed	Not listed	2B - Possible Human Carcinogen	titanium dioxide
Carbon black 2D Tossible Human Caremogen Not insted Elsted	Listed	Not listed	2B – Possible Human Carcinogen	carbon black

Per IARC Summary of Data Reported, Subsection 5.1: No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints.

Per IARC Summary of Data Reported, Subsection 5.1: No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as rubber, printing ink or paint.

### SECTION 12 : ECOLOGICAL INFORMATION

No ecological information available

## **SECTION 13 : DISPOSAL CONSIDERATION**

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Date issued: 8/24/2023

# SECTION 14 : TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

### **SECTION 15 : REGULATORY INFORMATION**

US TSCA:

Yes - All components are listed or exempt

### <u>Federal Regulations</u> SARA 311/312 hazardous categorization

Acute Health Hazard	YES
Chronic Health Hazard	NO
Fire Hazard	NO
Sudden Release of Pressure Hazard	NO
Reactive Hazard	NO

### **SARA 313**

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation Cas No. Weight %

Clean Air Act, Section 112 Hazardous Ai	r Pollutants (HAPS) (see 40 CFR 61)	
Chemical Designation	Cas No.	Weight %

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

### State Regulations

### **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

<b>Product Name:</b>	Insitu® Gray Waterborne Primer
<b>Product Code:</b>	WRA-AC-075

VER Primary

Date issued: 4/26/2016

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.